



LUZHONG 30-40HP TRACTOR MAIN SPECIFICATION

Model		LZ300B	LZ300B	LZ350B	LZ354B	LZ400B	LZ404B	
Type		4 x 2	4 x 4	4 x 2	4 x 4	4 x 2	4 x 4	
Dimensions of Tractor(mm)	Length (to front ballast)	3030						
	Width	1470						
	Height (to the exhaust vent)	1900						
	Tread	Front Wheel	1300 Fixed or 1100~1300 Adjusted					
		Rear Wheel	1300 Fixed or 1300~1350 Adjusted					
	Axle Base	1710						
Min.Ground Clearance	347.5							
Structure weight (kg)		1150						
Ballast weight (kg)	Front ballast	56						
	Rear ballast	112						
Rated traction force (N)		4460	5915	5200	6900	5940	7880	
Engine	Model	3100	3100	4L22	4L22	490	490	
	Type	Vertical,3-Cylinder,Water Cooled			Vertical,4-Cylinder,Water Cooled and 4-stroke			
	Rated Power(kw)	22.1	22.1	25.7	25.7	29.4	29.4	
	Rated speed (r/min)	2400						
	Fuel	Diesel						
Tyre	Front Wheel	6.50-16						
	Rear Wheel	11.2-24						
Clutch		Dual-stage clutch						
Steering		power steering						
Transmission Type		8+2 or 8+8 with shuttle gearshift or (8+2)x2 with creeper shift						
Suspension Type		3-point links						
PTO	Type and Rev	Semi-independent Type 540/1000						
	Spline Size	F35 Rectangle Spline with 6 teeth						

Structure and specification are subject to change without notice.

35HP TRACTOR

