



LUZHONG 60-65HP 2WD & 4WD TRACTOR MAIN SPECIFICATION

Model		LZ600	LZ650	LZ604	LZ654	
Type		2WD Wheeled Type		4WD Wheeled Type		
Dimensions of Tractor(mm)	Length (to front ballast)	3880				
	Width	1830				
	Height (to the exhaust vent)	2130				
	Tread	Front Wheel	1280			
		Rear Wheel	1300 Fixed or 1200~1500 Adjusted			
	Axle Base	2040				
Min.Ground Clearance		400		325		
Structure weight (kg)		1750	1750	2000	2000	
Ballast weight (kg)	Front ballast	140				
	Rear ballast	200				
PTO power at rated speed KW@rpm		39.6	43	39.6	43	
Engine	Model	4105				
	Type	Vertical,4-Cylinder,Water Cooled and 4-stroke				
	Rated Power(kw)	44.1	47.8	44.1	47.81	
	Rated speed (r/min)	2400				
	Fuel	Diesel				
Tyre	Front Wheel	650-16		8.3-24		
	Rear Wheel	14.9-28		14.9-28		
Clutch		Dual-stage clutch				
Steering		power steering				
Transmission Type		12+12 shuttle gearshift				
Suspension Type		3-point links				
PTO	Type and Rev	Semi-independent Type 540/1000				
	Spline Size	F35 Rectangle Spline with 6 teeth				

Structure and specification are subject to change without notice.

60-65HP TRACTOR

Models:

Luzhong-600 tractor, 60HP 2WD, with 4-cylinder diesel engine

Luzhong-604 tractor, 60HP 4WD, with 4-cylinder diesel engine

Luzhong-650 tractor, 65HP 2WD, with 4-cylinder diesel engine

Luzhong-654 tractor, 65HP 4WD, with 4-cylinder diesel engine

